

Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Screw locking E-COLL

· Article number: 4317784349192, 4317784179676

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Warning



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 1)

· Hazard-determining components of labelling:

2-hydroxyethyl methacrylate

2,2'-Ethylenedioxydiethyl dimethacrylate

2'-phenylacetohydrazide

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H413 May cause long lasting harmful effects to aquatic life.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	30-45%
CAS: 41637-38-1 EC number: 609-946-4 Reg.nr.: 01-2119980659-17	Bisphenol A ethoxylate dimethacrylate Aquatic Chronic 4, H413	30-45%
	<u> </u>	(Contd. on page 3



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

		(Contd. of page 2)
CAS: 109-16-0	2,2'-Ethylenedioxydiethyl dimethacrylate	1-5%
EINECS: 203-652-6	(1) Skin Sens. 1, H317	
Reg.nr.: 01-2119969287-21-xxxx		
CAS: 80-15-9	α,α -dimethylbenzyl hydroperoxide	<1.5%
EINECS: 201-254-7	♠ Org. Perox. E, H242	
Index number: 617-002-00-8	Acute Tox. 3, H331	
Reg.nr.: 01-2119475796-19-xxxx	STOT RE 2, H373	
Ĭ	Skin Corr. 1B, H314	
	Aquatic Chronic 2, H411	
	Acute Tox. 4, H302; Acute Tox. 4, H312	
	Specific concentration limits:	
	Skin Corr. 1B; H314: C ≥ 10%	
	Skin Irrit. 2; H315: 3 % ≤ C < 10 %	
	Eye Dam. 1; H318: C ≥ 3 %	
	Eye Irrit. 2; H319: 1 % ≤ C < 3 %	
	STOT SE 3; H335: C < 10 %	
CAS: 114-83-0	2'-phenylacetohydrazide	0.1-<0.5%
EINECS: 204-055-3	Acute Tox. 3, H301	0.1-<0.576
LINECS. 204-033-3	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1,	
	H317; STOT SE 3, H335	
0.00 400 04.0	,	0.04.0.050/
CAS: 123-31-9	1,4-dihydroxybenzene	0.01-<0.05%
EINECS: 204-617-8	& Muta. 2, H341; Carc. 2, H351	
Index number: 604-005-00-4	Eye Dam. 1, H318	
	Aquatic Acute 1, H400 (M=10)	
	🗘 Acute Tox. 4, H302; Skin Sens. 1, H317	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Sulphur dioxide (SO2)

- · 5.3 Advice for firefighters
- Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Avoid splashes or spray in enclosed areas.

Use solvent-proof equipment.

(Contd. on page 5)



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 4)

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Use only receptacles specifically permitted for this substance/product.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

CAS: 109-16-0 2,2'-Ethylenedioxydiethyl dimethacrylate

Dermal Long term value for employees 13.9 mg/kg bw/Tag /AF-72 (industrial use)

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the skin.

Avoid contact with the eyes.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A/P2

(Contd. on page 6)



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 5)

· Hand protection



· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Recommendation: safety glasses with side protection shield
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour: Green
 Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: > 100 °C

• **Decomposition temperature:** Not determined.

· pH at 20 °C 5

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 <0.5 mbar

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

(Contd. on page 7)



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 6)

Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

Solvent separation test:

· Organic solvents: 0.0 %

· Change in condition

· Softening point/range

Oxidising propertiesEvaporation rateNot determined.Not determined.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water Oxidising liquids Void Oxidising solids Void Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with strong oxidising agents.

Danger of polymerisation.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
CAS: 868	CAS: 868-77-9 2-hydroxyethyl methacrylate		
Oral	LD50	5,050 mg/kg (rat)	
CAS: 80-15-9 α,α -dimethylbenzyl hydroperoxide			
Oral	LD50	382 mg/kg (rat)	
Dermal	LD50	500 mg/kg (rat)	
Inhalative	LC50/4h	220 ppm (rat)	
CAS: 114	CAS: 114-83-0 2'-phenylacetohydrazide		
Oral	LD50	270 mg/kg (mouse)	
CAS: 123	CAS: 123-31-9 1,4-dihydroxybenzene		
Oral	LD50	320 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 8)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:				
CAS: 41637-38-1 Bisphenol A ethoxylate dimethacrylate				
EL50/48h	100 mg/l (daphnia)			
EL50/72h	100 mg/l (Pseudokirchneriella subcapitata)			
CAS: 80-15-9 α,α -dimethylbenzyl hydroperoxide				
LC50 (96h)	3.9 mg/L (Oncorhynchus mykiss)			
EC50/24h	7 mg/l (daphnia)			
CAS: 123-31-9 1,4-dihydroxybenzene				
EC50/24h	0.12 mg/l (daphnia)			
96h LC50	0.044 mg/l (Pimephales promelas)			

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, ADN, IMDG, IATA

Void



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 9)

· 14.2 UN proper shipping name

· ADR UN-· ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR

Class - (-)
 Label ADN/R Class: Void

· IMDG, IATA

· Class Void · Label -

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· UN "Model Regulation": UN-, -

SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

- Signal word Warning
- · Hazard-determining components of labelling:

2-hydroxyethyl methacrylate

2,2'-Ethylenedioxydiethyl dimethacrylate

2'-phenylacetohydrazide

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H413 May cause long lasting harmful effects to aquatic life.

(Contd. on page 11)



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 10)

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. P337+P313

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Department issuing SDS: Product safety department

· Contact: sdb@ede.de

· Date of previous version: 14.02.2023 · Version number of previous version: 303

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent



Printing date 14.02.2023 Version number 304 (replaces version 303) Revision: 14.02.2023

Trade name: Screw locking E-COLL

(Contd. of page 11)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. E: Organic peroxides – Type E/F Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

· * Data compared to the previous version altered.

EU